

SG12864H (128 DOTS X 64 DOTS)

FEATURES

- . BUILT-IN CONTROLLER (KS0107 OR EQUIVALENT)
- . +5 V POWER SUPPLY
- . 1/64 DUTY CYCLE
- . 8-BIT PARALLEL INTERFACE

MECHANICAL DATA

ITEM	DIMENSIONS	UNIT
Module Size (W x H x T)	75.0 x 52.7 x 7.9 (9.2 LED)	mm
Viewing Area (W x H)	60.0 x 32.5	mm
Active Area (W x H)	55.01 x 27.49	mm
Dot Size (W x H)	0.40 x 0.40	mm
Dot Pitch (W x H)	0.43 x 0.43	mm

INTERFACE PIN CONNECTIONS

NO.	SYMBOL	LEVEL	FUNCTION
1	V _{DD}	5V	Power Supply Voltage
2	V _{SS}	0V	Power Supply Ground
3	V ₀	-	Contrast Adjustment Voltage
4~11	DB0-DB7	H/L	Data Bus Line
12	CS1	H	Chip Select Signal For IC1
13	CS2	H	Chip Select Signal For IC2
14	/RES	L	Reset Signal
15	R/W	H/L	H : Read / L : Write
16	D/I	H/L	L : Data, H : Instruction Code
17	E	H→L	Enable Signal
18	V _{out}	-	Power Supply Voltage For LCD
19	A	4.2V	LED Power (+)
20	K	0V	LED Power (-)

ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage For Logic	V _{DD} -V _{SS}	0	-	7	V
Supply Voltage For LCD Drive	V _{DD} -V ₀	0	-	18	V
Input Voltage	V _I	V _{SS}	-	V _{DD}	V

ELECTRICAL CHARACTERISTICS

ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	
Supply Voltage For Logic	V _{DD} -V _{SS}	-	4.5	5	5.5	V	
Supply Voltage For LCD	V _{DD} -V ₀	V _{DD} =5V Ta=25.	7.8	8.6	9.2	V	
Supply Current	I _{DD}	V _{DD} =5V	-	6.2	10	mA	
Input Voltage	"HIGH" Level	V _{IH}	-	2.2	-	V _{DD}	V
	"LOW" Level	V _{IL}	-	-	-	0.6	V
Output Voltage	"HIGH" Level	V _{OH}	-	2.4	-	-	V
	"LOW" Level	V _{OL}	-	-	-	0.4	V

EXTERNAL DIMENSIONS

